


MODEL: ~~2088-564-144~~

2088-594-444


### SPECIFICATIONS:

**MODEL NUMBER:** 2088-564-144  
**PUMP DESIGN:** Positive Displacement 3 Chamber Diaphragm Pump  
**CHECK VALVE:** (1-Way Operation) Prevents Reverse Flow  
**CAM:** 3.0 Degree  
**MOTOR:** Permanent Magnet, P/N 11-160-10, Thermally Protected  
**VOLTAGE:** 230 VAC Nominal *, CE, UL*  
**PRESSURE SWITCH:** Factory Set @ 45 PSI Shut-Off, Turn On 25 ± 5 PSI  
**LIQUID TEMPERATURE:** 130 Degrees Fahrenheit (54 Degrees Centigrade) Max.  
**PRIME:** Self-Priming Up To 9.0 Ft. Vertical,  
 Max. Inlet Pressure 30 PSI (2.1 Bar)  
**PORTS:** 1/2" - 14 Male Parallel Thread  
**MATERIAL OF CONSTRUCTION:**  
 PLASTICS- Polypropylene  
 VALVES- Santoprene  
 DIAPHRAGM- Santoprene  
 FASTENERS- Zinc Plated Steel  
**NET WEIGHT:** 5.0 Lbs (2.27 Kg)  
**DUTY CYCLE:** Intermittent (See Temp. Rise Chart)  
**TYPICAL APPLICATIONS:** Water Delivery  
**APPROVALS:** N.S.F. Listed

### DIMENSIONS:




### TEMPERATURE RISE



THIS GRAPH IS FOR USE AS A DESIGN GUIDE. IT IS BASED ON RUNNING CONTINUOUSLY WITH AN AMBIENT TEMPERATURE OF 75 °F IN STILL AIR. THE THERMAL BREAKER WILL OPEN WHEN THE CASE TEMPERATURE REACHES 250°F.

[---- TRIP POINT OF THERMAL PROTECTOR]

### TYPICAL PERFORMANCE



PRESSURE (PSI)	FLOW (GPM/LIT)	RPM MIN/MAX	CURRENT (AMPS)	VOLTAGE (VOLTS)
OPEN	3.00/11.3	2140/2150	.30	230VAC
10	2.80/10.6	2115/2140	.35	"
20	2.50/9.5	1995/2010	.45	"
30	2.20/8.3	1895/1910	.50	"
40	2.00/7.6	1795/1825	.55	"
50	1.70/6.4	1695/1755	.60	"

-SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.  
 -ALL DATA BASED ON TESTING WITH WATER.