

SOLAR SUBMERSIBLE PUMPS

Remote Water Pumping Applications



- 12 VDC or 24 VDC Operation
- Steady Delivery 310LPH (82GPH)
- Total Lift Height of 70m (230 ft.)
- Submersible to 30m (100 ft.)
- Runs Dry without Damage
- For 4" Wells or Larger
- Corrosion-Proof Housing
- 50 Mesh Stainless Steel Screen
- Low Maintenance- Easily Repaired in the Field



9325-Series

Contact Information (EMEA):

Phone: +32-14-283-500

Fax: +32-14-283-505

Email: shurflo@pentair.com

Web site: www.shurflo.com

Web site: www.pentair.com

SOLAR PUMP CONTROLLERS

Boost DC Solar Pump Performance



- 12 VDC or 24 VDC Operation
- Increases Daily Water Output up to 30%
- System Starts Pumping Earlier in the Morning
- System Stops Pumping Later in the Evening
- Protects Pump from Low or High Voltage
- Terminals for Float Switch
- Pump On-Off Switch (Optional)
- Water-Tight Enclosure and Cable Inlets (Optional)
- Water Level Monitor Mode with Probes and Cable (Optional)



LCB-Series

Contact Information (EMEA):

Pentair Water Belgium bvba

Industriepark Wolfstee

Toekomstlaan 30

B-2200 Herentals

Belgium



- Self-Priming up to 3.7m (12 ft.)
- Steady Delivery up to 14.3 LPM (3.8 GPM)
- Available in a Voltages from 12VDC to 230VAC
- Can Run Dry without Damage
- Automatic Demand
- Built-in Check Valve to Prevent Back Flow



2088-Series

Contact Information (EMEA):
 Phone: +32-14-283-500
 Fax: +32-14-283-505
 Email: shurflo@pentair.com
 Web site: www.shurflo.com
 Web site: www.pentair.com



- Self-Priming up to 2.4m (8 ft.)
- Steady Delivery up to 19 LPM (5 GPM)
- Available in 12VDC or 24VDC
- Can Run Dry without Damage
- Heavy Duty Sealed Motor
- Bypass for Smooth Flow
- Co-Molded Diaphragm
- Compact 4-Chamber Design
- Built-in Check Valve to Prevent Back Flow
- Sealed Switch

NEW !



5050-Series

Contact Information (EMEA):
 Pentair Water Belgium bvba
 Industriepark Wolfstee
 Toekomstlaan 30
 B-2200 Herentals
 Belgium